

INSTALLATION INSTRUCTIONS

For Model # 1687-14 (New. 01/23/2003)

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

MOUNTING THE FIXTURE (Fig.1)

1. Shut off power at the circuit breaker and remove old fixture from ceiling, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Thread two Studs (E) about 1/4" into the pre-drilled holes in the Circular Strap (D) spaced the same distance apart as the holes in the canopy of Fixture Body.
4. Attach the Circular Strap (D) to the Outlet Box (G) using the two Screws (F). The side of the Circular Strap marked "GND" must face out.
5. Hang the fixture by placing Fixture Body (C) over both Studs (E) and secure Fixture Body against ceiling with Knurled Knobs (H).

CONNECTING THE WIRES (Fig.2)

6. While holding the Fixture Body (C) towards the ceiling, connect the electrical wires as shown in Fig.2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's Ground Wire to it. Otherwise, connect the fixture's Ground Wire directly to the Circular Strap using the Green Screw provided. After wires are connected, tuck them carefully into the ceiling Junction Box.

SHADE INSTALLATION (Fig. 1)

7. Install the light bulb in accordance with fixtures specifications. **(CAUTION: Do not exceed the maximum wattage rating!)**
8. Place the Glass Shade (B) into the Shade Frame (A).
9. Attach Shade Frame (A) with Glass Shade (B) inside onto the Fixture Body (C) using joints of Fixture Body as shown in Fig. 1.

Fig. 1





Fig. 2



american
lighting
association

Your installation is now complete. Return power to the junction box and test the fixture.

LA-662E